


*The 6<sup>th</sup> International Conference - Channeling 2014  
Charged & Neutral Particles Channeling Phenomena  
October 5<sup>th</sup>-10<sup>th</sup>, 2014, Capri (Naples), Italy*

# Goals and Plans for the Crystal Collimation Test at the Large Hadron Collider

***Stefano Redaelli, CERN, BE-ABP  
on behalf of the Collimation Project and the UA9 teams***



*The HiLumi LHC Design Study is included in the High Luminosity LHC project and is partly funded by the European Commission within the Framework Programme 7 Capacities Specific Programme, Grant Agreement 284404.*





# Outline



- Introduction**
- LHC beam collimation**
- Crystal collimation**
- Layouts for beam tests**
- Plans for 2015**
- Conclusions**




# Acknowledgements

This talk is given on behalf of the members of  
the LHC collimation team  
the UA9 collaboration

Special thanks to  
Walter Scandale  
Daniele Mirarchi

# Introduction




*Superconducting coil:  
 $T = 1.9 \text{ K}$ , quench limit  
 $\sim 15\text{-}50 \text{ mJ/cm}^3$*

*Factor  $9.7 \times 10^9$   
Aperture:  $r = 17/22 \text{ mm}$*

*LHC 2012: 145 MJ  
LHC design: 360 MJ  
HL-LHC:  $\sim 700 \text{ MJ}$ !*

# Introduction



*Superconducting coil:  
 $T = 1.9 \text{ K}$ , quench limit  
 $\sim 15\text{-}50 \text{ mJ/cm}^3$*

*Factor  $9.7 \times 10^9$   
Aperture:  $r = 17/22 \text{ mm}$*

*LHC 2012: 145 MJ  
LHC design: 360 MJ  
HL-LHC:  $\sim 700 \text{ MJ}$ !*

**LHC "Run 1" 2010-2013: No quench with circulating beam, with stored energies up to 70 times of previous state-of-the-art!**



# Roles of LHC collimation system





# Roles of LHC collimation system



- **Halo cleaning**: reduce the risk of magnet quenches



# Roles of LHC collimation system



- **Halo cleaning**: reduce the risk of magnet quenches
- **Passive machine protection**  
*Collimators are the first line of defense in case of accidental failures.*





# Roles of LHC collimation system



- **Halo cleaning**: reduce the risk of magnet quenches
- **Passive machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*



# Roles of LHC collimation system



- **Halo cleaning**: reduce the risk of magnet quenches
- **Passive machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*
- **Reduction total doses** on accelerator equipment  
*Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)*



# Roles of LHC collimation system



- **Halo cleaning**: reduce the risk of magnet quenches
- **Passive machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*
- **Reduction total doses** on accelerator equipment  
*Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)*
- **Cleaning of physics debris** (collision products)  
*Avoid SC magnet quenches close to the high-luminosity experiments*



# Roles of LHC collimation system



- **Halo cleaning**: reduce the risk of magnet quenches
- **Passive machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*
- **Reduction total doses** on accelerator equipment  
*Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)*
- **Cleaning of physics debris** (collision products)  
*Avoid SC magnet quenches close to the high-luminosity experiments*
- Optimize **background** in the experiments  
*Minimize the impact of halo losses on  
(no big issue for the LHC)*




# Roles of LHC collimation system




- **Halo cleaning**: reduce the risk of magnet quenches
- **Passive machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*
- **Reduction total doses** on accelerator equipment  
*Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)*
- **Cleaning of physics debris** (collision products)  
*Avoid SC magnet quenches close to the high-luminosity experiments*
- Optimize **background** in the experiments  
*Minimize the impact of halo losses on  
(no big issue for the LHC)*
- Beam tail/halo **scraping, halo diagnostics**  
*Control and probe the transverse or longitudinal shape of the beam*


# LHC multi-stage collimation



# LHC multi-stage collimation




# LHC multi-stage collimation





# LHC multi-stage collimation



Including protection devices, a **5-stage cleaning** is required!

The system performance relies on achieving the well-defined **hierarchy** between collimator families and machine aperture.



# Collimation layout for the LHC Run II



**Two warm cleaning insertions,  
3 collimation planes**

**IR3: Momentum cleaning**

- 1 primary (H)
- 4 secondary (H)
- 4 shower abs. (H,V)

**IR7: Betatron cleaning**

- 3 primary (H,V,S)
- 11 secondary (H,V,S)
- 5 shower abs. (H,V)

**Local cleaning at triplets**

8 tertiary (2 per IP)


Passive absorbers for warm magnets

Physics debris absorbers


Transfer lines (13 collimators)

Injection and dump protection (10)


**Total of 118 collimators (108 movable).  
Two jaws (4 motors) per collimator!**



# Collimator gaps in 2012




# Collimator gaps in 2012



*2012: achieved the our design 7 TeV primary collimator setting!  
Secondary collimator retraction still above nominal ( $\sim 2.5\sigma$  retraction instead than  $1\sigma$ ).  
Possible limitations: **impedance** and **OP efficiency** (more frequent alignments).*

# Collimator gaps in 2012




2012: achieved the our design 7 TeV primary collimator setting!  
 Secondary collimator retraction still above nominal ( $\sim 2.5\sigma$  retraction instead than  $1\sigma$ ).  
 Possible limitations: **impedance** and **OP efficiency** (more frequent alignments).

$\sigma_v = 250$  microns!


60 cm flat active length, gap =  $\pm 1.05$  mm

1 pound






# Collimator movements in operation




# Collimator movements in operation



**LHC requires continuous collimation from injection to collisions!**  
 Collimators follow the beam evolution during energy and optics changes.




# Collimation cleaning at 4 TeV ( $\beta^*=60\text{cm}$ )








# Collimation cleaning at 4 TeV ( $\beta^*=60\text{cm}$ )



**Highest COLD loss location: efficiency of > 99.99% !  
Most of the ring actually > 99.999%**


# Collimation cleaning in IR7



B. Salvachua

Critical locations (both beams): losses in the dispersion suppressors around (Q8) from single diffractive interactions with the primary collimators.  
 No other major cleaning limitations observed around the ring with present optics.

# Collimation cleaning in IR7




B. Salvachua

Present estimate of intensity reach at the LHC from betatron cleaning: at 6.5TeV can reach **3x-6x the nominal LHC intensity**. Margins reduced for HL-LHC. Depending on quench limit, we might have no issue!

Critical locations (both be from single diffractive inte No other major cleaning li


# Betatron cleaning for Pb ion beams



Betatron cleaning of a few percent: **factor ~100 worst** than for protons.

**Limiting location** still the **dispersion suppressor**, but different loss distribution than for protons: ion beams from dissociation and fragmentation at the primary collimators are lost at specific locations.

# Betatron cleaning for Pb ion beams



Betatron cleaning of a few percent: **factor ~100 worst** than for protons.

**Limiting location** still the **dispersion suppressor**, but different loss distribution than for protons: ion beams from dissociation and fragmentation at the primary collimators are lost at specific locations.




# Outline




- Introduction
- LHC beam collimation
- Crystal collimation**
- Layouts for beam tests
- Plans for 2015
- Conclusions

# Concept of crystal collimation (i)



*Bent crystals allow bending high-energy particles trapped between lattice planes.*



*Bent crystals allow bending high-energy particles trapped between lattice planes.*


Application for **hadron beam collimation**:

Crystals might be used as primary collimators to **exploit large angles** ( $\sim 50\mu\text{rad}$ ) and the **reduced change of beam rigidity** (diffractive events and ion dissociation/fragmentation).

## Challenges for the LHC:

- small angular acceptance;
- localization of large losses (0.5-1.0MJ) in one single collimator.





*Bent crystals allow bending high-energy particles trapped between lattice planes.*

Application for **hadron beam collimation**:

Crystals might be used as primary collimators to **exploit large angles** ( $\sim 50\mu\text{rad}$ ) and the **reduced change of beam rigidity** (diffractive events and ion dissociation/fragmentation).

## Challenges for the LHC:

- small angular acceptance;
- localization of large losses (0.5-1.0MJ) in one single collimator.

*Solid experimental validation at the SPS from UA9 experiment (starting in 2009), at beam energies up to 270 GeV (proton and ion beams).  
 (less positive results in other machines like RHIC and Tevatron...)*



# Crystals for LHC collimation



- **Halo cleaning**: reduce the risk of magnet quenches
- Passive **machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*
- **Reduction total doses** on accelerator equipment  
*Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)*
- **Cleaning of physics debris** (collision products)  
*Avoid SC magnet quenches close to the high-luminosity experiments*
- Optimize **background** in the experiments  
*Minimize the impact of halo losses on  
(no big issue for the LHC)*
- Beam tail/halo **scraping, halo diagnostics**  
*Control and probe the transverse or longitudinal shape of the beam*


- **Halo cleaning**: reduce the risk of magnet quenches
- Passive **machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*
- **Reduction total doses** on accelerator equipment  
*Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)*
- **Cleaning of physics debris** (collision products)  
*Avoid SC magnet quenches close to the high-luminosity experiments*
- Optimize **background** in the experiments  
*Minimize the impact of halo losses on  
(no big issue for the LHC)*
- Beam tail/halo **scraping, halo diagnostics**  
*Control and probe the transverse or longitudinal shape of the beam*

- **Halo cleaning**: reduce the risk of magnet quenches
- Passive **machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*
- **Reduction total doses** on accelerator equipment  
*Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)*
- **Cleaning of physics debris** (collision products)  
*Avoid SC magnet quenches close to the high-luminosity experiments*
- Optimize **background** in the experiments  
*Minimize the impact of halo losses on  
(no big issue for the LHC)*
- Beam tail/halo **scraping, halo diagnostics**  
*Control and probe the transverse or longitudinal shape of the beam*

- **Halo cleaning**: reduce the risk of magnet quenches
- Passive **machine protection**  
*Collimators are the first line of defense in case of accidental failures.*
- **Concentration of losses/activation** in controlled areas  
*Avoid many hot locations around the 27km-long tunnel*
- **Reduction total doses** on accelerator equipment  
*Provide local protection to equipment exposed to high doses (like the warm magnets in cleaning insertions)*
- **Cleaning of physics debris** (collision products)  
*Avoid SC magnet quenches close to the high-luminosity experiments*
- Optimize **background** in the experiments  
*Minimize the impact of halo losses on  
(no big issue for the LHC)*
- Beam tail/halo **scraping, halo diagnostics**  
*Control and probe the transverse or longitudinal shape of the beam*




# Concept of crystal collimation (ii)

Standard multi-stage collimation




# Concept of crystal collimation (ii)

## Standard multi-stage collimation




## Ideal crystal-based collimation




# Concept of crystal collimation (ii)

## Standard multi-stage collimation



## Ideal crystal-based collimation




Promises of crystal collimation at the LHC:

1. Improve **collimation cleaning** achieved with fewer collimators;
2. Reduce electro-magnetic perturbations of collimators to the beams (**impedance**);
3. Improve significantly the cleaning for **ion beams**.



# Concept of crystal collimation (ii)


## Standard multi-stage collimation



Promises of crystal collimation at the LHC:

1. Improve **collimation cleaning** achieved with fewer collimators;
2. Reduce electro-magnetic perturbations of collimators to the beams (**impedance**);
3. Improve significantly the cleaning for **ion beams**.

## Ideal crystal-based collimation



*Can this really work at the LHC?*



*Beam tests deemed necessary before relying on crystal collimation...*



# Goals of beam tests at the LHC





# Goals of beam tests at the LHC



- ☑ Demonstrate hadron beam channeling at **larger energies** with the required **efficiency!**

*There are uncertainties in the extrapolation to **unknown energy territories**.  
Both for protons and for ion beams.*



# Goals of beam tests at the LHC



- ☑ Demonstrate hadron beam channeling at **larger energies** with the required **efficiency!**

*There are uncertainties in the extrapolation to **unknown energy territories**.  
Both for protons and for ion beams.*

- ☑ Demonstrate that crystal collimation can **improve the cleaning performance** compared to present system!

*We have seen that the betatron cleaning worked very well so far!*



# Goals of beam tests at the LHC



- ☑ Demonstrate hadron beam channeling at **larger energies** with the required **efficiency!**

*There are uncertainties in the extrapolation to **unknown energy territories**.  
Both for protons and for ion beams.*

- ☑ Demonstrate that crystal collimation can **improve the cleaning performance** compared to present system!

*We have seen that the betatron cleaning worked very well so far!*

- ☑ Demonstrate the feasibility of **crystal alignment** at the required angular tolerances



# Goals of beam tests at the LHC



- ☑ Demonstrate hadron beam channeling at **larger energies** with the required **efficiency!**  
*There are uncertainties in the extrapolation to **unknown energy territories**. Both for protons and for ion beams.*
- ☑ Demonstrate that crystal collimation can **improve the cleaning performance** compared to present system!  
*We have seen that the betatron cleaning worked very well so far!*
- ☑ Demonstrate the feasibility of **crystal alignment** at the required angular tolerances
- ☑ Demonstrate that crystal collimation can work during **all operational phases**, as required at the LHC.  
*Beam tests so far performed with coasting beams.  
LHC require a performing cleaning during injection, ramp, squeeze, ...*

# Goals of beam tests at the LHC

- ☑ Demonstrate hadron beam channeling at **larger energies** with the required **efficiency!**  
*There are uncertainties in the extrapolation to **unknown energy territories**. Both for protons and for ion beams.*
- ☑ Demonstrate that crystal collimation can **improve the cleaning performance** compared to present system!  
*We have seen that the betatron cleaning worked very well so far!*
- ☑ Demonstrate the feasibility of **crystal alignment** at the required angular tolerances
- ☑ Demonstrate that crystal collimation can work during **all operational phases**, as required at the LHC.  
*Beam tests so far performed with coasting beams.  
LHC require a performing cleaning during injection, ramp, squeeze, ...*

A crystal collimation test with LHC beams if foreseen to address these open points!

Scope of **first phase**: feasibility demonstration at **low-intensity!**



# Goals of beam tests at the LHC



- ☑ Demonstrate hadron beam channeling at **larger energies** with the required **efficiency!**  
*There are uncertainties in the extrapolation to **unknown energy territories**. Both for protons and for ion beams.*
- ☑ Demonstrate that crystal collimation can **improve the cleaning performance** compared to present system!  
*We have seen that the betatron cleaning worked very well so far!*
- ☑ Demonstrate the feasibility of **crystal alignment** at the required angular tolerances
- ☑ Demonstrate that crystal collimation can work during **all operational phases**, as required at the LHC.  
*Beam tests so far performed with coasting beams.  
LHC require a performing cleaning during injection, ramp, squeeze, ...*

A crystal collimation test with LHC beams if foreseen to address these open points!

Scope of **first phase**: feasibility demonstration at **low-intensity!**

*In parallel: need to address high-energy challenge (0.5-1.0 MW losses in single absorber)*





# Outline



- Introduction
- LHC beam collimation
- Crystal collimation
- Layouts for beam tests**
- Plans for 2015
- Conclusions



# Crystal layout design in IR7



Recent development, in addition to the years of experience from UA9:


- **Improved tools** to identify suitable candidate layouts (semi-analytical analysis of channeled beam trajectories).
- **Setup complete tracking simulations to predict loss maps**
  - Important to address cleaning performance taking into account layout constraints and leakage from collimators used as absorbers.
- Worked on an **improved crystal routine** for tracking studies.
- Conceived set of setting for the whole collimation system (~50 collimators) to achieve PhD thesis work by D. Mirarchi (see his talk later)




# Crystal layout design in IR7



# Crystal layout design in IR7




# Crystal layout design in IR7



Ideally: install crystal at location with **zero derivative** of beam envelope  
 → *same angle versus energy!*

# Crystal layout design in IR7



Ideally: install crystal at location with **zero derivative** of beam envelope


→ *same angle versus energy!*

**Optics changes** are very **costly** in terms of commissioning **time** at the LHC!

→ *taken the design choice to use present optics to avoid commissioning overheads.*

→ *direct comparison of cleaning performance against present collimation.*

# Crystal layout design in IR7



Ideally: install crystal at location with **zero derivative** of beam envelope

→ *same angle versus energy!*

**Optics changes** are very **costly** in terms of commissioning **time** at the LHC!

→ *taken the design choice to use present optics to avoid commissioning overheads.*

→ *direct comparison of cleaning performance against present collimation.*

Rely on **existing collimation** system to catch the secondary beams

→ **only compatible with low-intensity beams.**



# Key layout features



<b>Collimation plane</b>	<b>Bending [<math>\mu\text{rad}</math>]</b>	<b>Length [mm]</b>	<b>Material</b>	<b>Bending planes</b>
Hor.	50	4	Si	110
Ver.	50	4	Si	111





# Key layout features

- ☑ Initial installation (carried out in April 2014):
  - Two goniometers on beam 1 only (horizontal + vertical)
  - Preparation of infrastructure for additional detectors
  - Improved beam instrumentation (fast diamond loss monitors)

<b>Collimation plane</b>	<b>Bending [<math>\mu\text{rad}</math>]</b>	<b>Length [mm]</b>	<b>Material</b>	<b>Bending planes</b>
Hor.	50	4	Si	110
Ver.	50	4	Si	111

# Key layout features

- ☑ Initial installation (carried out in April 2014):
  - Two goniometers on beam 1 only (horizontal + vertical)
  - Preparation of infrastructure for additional detectors
  - Improved beam instrumentation (fast diamond loss monitors)
- ☑ Crystal angle in both planes: **50  $\mu$ rad** (see table)

Collimation plane	Bending [ $\mu$ rad]	Length [mm]	Material	Bending planes
Hor.	50	4	Si	110
Ver.	50	4	Si	111

# Key layout features

- ☑ Initial installation (carried out in April 2014):
  - Two goniometers on beam 1 only (horizontal + vertical)
  - Preparation of infrastructure for additional detectors
  - Improved beam instrumentation (fast diamond loss monitors)
- ☑ Crystal angle in both planes: **50  $\mu$ rad** (see table)
- ☑ Crystal collimation layout suitable for beam tests from injection energy (450 GeV) to top energy (6.5 TeV in 2015)

*Different collimator configurations required to intercept the channeled beam.*

Collimation plane	Bending [ $\mu$ rad]	Length [mm]	Material	Bending planes
Hor.	50	4	Si	110
Ver.	50	4	Si	111

# Key layout features


- ☑ Initial installation (carried out in April 2014):
  - Two goniometers on beam 1 only (horizontal + vertical)
  - Preparation of infrastructure for additional detectors
  - Improved beam instrumentation (fast diamond loss monitors)
- ☑ Crystal angle in both planes: **50  $\mu\text{rad}$**  (see table)
- ☑ Crystal collimation layout suitable for beam tests from injection energy (450 GeV) to top energy (6.5 TeV in 2015)

*Different collimator configurations required to intercept the channeled beam.*
- ☑ Possibility to improve cleaning relies on 5 other absorber collimators.


*A Carbon-based collimator is used to intercept the beam: not enough absorption for cleaning!*

Collimation plane	Bending [ $\mu\text{rad}$ ]	Length [mm]	Material	Bending planes
Hor.	50	4	Si	110
Ver.	50	4	Si	111


# Installation status



*Sketch of crystal goniometer in the LHC cleaning insertion IR7*




Beam 1



Beam 1

# Goniometer design concept



*Design derived from some LHC beam instrumentation: with high intensity beams, a ‘C’ vacuum chamber “hides” the goniometer (only moved in beam for dedicated beam tests).*



*We designed the hardware with the goal of being “transparent” for the standard LHC operation. This also simplified the design versus impedance and vacuum constraints!*





*Courtesy W. Scandale, A. Masi  
Dedicated talk by A Masi in this session!*

# Expected crystal collimation cleaning



See talk later by D. Mirarchi for complete simulation setup.

# Expected crystal collimation cleaning







# Outline



- Introduction
- LHC beam collimation
- Crystal collimation
- Layouts for beam tests
- Plans for 2015**
- Conclusions

# Baseline 2015 schedule (i)

	Jan			Feb				Mar					
Wk	1	2	3	4	5	6	7	8	9	10	11	12	13
Mo	29	5	12	19	26	2	9	16	23	2	9	16	23
Tu													
We				HW tests									
Th											Recommissioning with beam		
Fr													
Sa													
Su						Sector test (S23)		Sector test (S78)					

	Apr			May				June					
Wk	14	15	16	17	18	19	20	21	22	23	24	25	26
Mo	30	6	13	20	27	4	11	18	25	1	8	15	22
Tu													
We							LHCf VdM		TS1				
Th	Recommissioning with beam									Intensity ramp-up with 50 ns beam			
Fr													
Sa													
Su													

Scrubbing for 50 ns operation (May 21)      Scrubbing for 25 ns operation (June 25)

Commissioning strategy recently discussed at the “Chamonix” LHC Performance Workshop (Sep. 22<sup>nd</sup>-25<sup>th</sup>).

Start of beam commissioning: **March 2015**

M. Lamont, J. Wenninger,



□ The main strategy for 2015 is to concentrate on 6.5 TeV and 25 ns beam to reduce complexity:

- Relaxed  $\beta^*$  of 80 cm for the startup
- Plan a change of  $\beta^*$  later during the run.

→ Necessary beam time to be allocated to understand the LHC after the 2 year stop!

**Explore in 2015, produce in 2016 !**

# Baseline 2015 schedule (ii)



MD = Machine Development → beam studies for various purposes (immediate performance improvement, long-term developments, test new concepts, ...)



# Main goals for first studies in 2015





# Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...



# Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:



# Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- Establish channeling and demonstrate improved cleaning at **injection energy.**



# Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- ☑ Establish channeling and demonstrate improved cleaning at **injection energy**.
- ☑ Establish channeling and demonstrate improved cleaning at **top-energy (6.5 TeV)**.

*This includes verification of angular stability.*





# Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- ☑ Establish channeling and demonstrate improved cleaning at **injection energy**.
- ☑ Establish channeling and demonstrate improved cleaning at **top-energy (6.5 TeV)**.

*This includes verification of angular stability.*

- ☑ Check crystal performance with **Pb ion beams**.



# Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- ☑ Establish channeling and demonstrate improved cleaning at **injection energy**.
- ☑ Establish channeling and demonstrate improved cleaning at **top-energy (6.5 TeV)**.  
*This includes verification of angular stability.*
- ☑ Check crystal performance with **Pb ion beams**.
- ☑ *If possible, check crystal collimation in **dynamics operational phases** like ramp and squeeze.*



# Main goals for first studies in 2015



Assuming that the new hardware is thoroughly tested at the SPS and in the lab (2 goniometers bought for this purpose)...

Assuming that we get 2-3 shifts in the main MD blocks:

- ☑ Establish channeling and demonstrate improved cleaning at **injection energy**.
- ☑ Establish channeling and demonstrate improved cleaning at **top-energy (6.5 TeV)**.

*This includes verification of angular stability.*

- ☑ Check crystal performance with **Pb ion beams**.
- ☑ *If possible, check crystal collimation in **dynamics operational phases** like ramp and squeeze.*

Very ambitious program!  
Cannot effort hardware and software debugging during LHC beam time!



# Conclusions





# Conclusions

- ☑ The present **LHC collimation system**, and highlight of its main performance achievements, were presented.

*We are very happy with the performance up to 4 TeV → legacy for upgrades!*

*We need to monitor carefully the behaviour at higher energies (quenches!)*



# Conclusions

- ☑ The present **LHC collimation system**, and highlight of its main performance achievements, were presented.

*We are very happy with the performance up to 4 TeV → legacy for upgrades!*

*We need to monitor carefully the behaviour at higher energies (quenches!)*

- ☑ Scope of a possible **crystal collimation** at the LHC were introduced.

*Beam tests in the LHC deemed necessary before relying on this promising technique for LHC upgrades and for other machines.*

# Conclusions

- ☑ The present **LHC collimation system**, and highlight of its main performance achievements, were presented.

*We are very happy with the performance up to 4 TeV → legacy for upgrades!  
We need to monitor carefully the behaviour at higher energies (quenches!)*

- ☑ Scope of a possible **crystal collimation** at the LHC were introduced.

*Beam tests in the LHC deemed necessary before relying on this promising technique for LHC upgrades and for other machines.*

- ☑ A setup for crystal collimation studies has been **installed** in the LHC collimation insertion region for **beam tests** starting in **2015!**

*We believe that we can learn a lot for a minimum-impact installation setup with goniometers for horizontal and vertical beam tests.*

*Other outstanding open points will follow this “first phase” at low intensities.*

# Conclusions

- ☑ The present **LHC collimation system**, and highlight of its main performance achievements, were presented.

*We are very happy with the performance up to 4 TeV → legacy for upgrades!  
We need to monitor carefully the behaviour at higher energies (quenches!)*

- ☑ Scope of a possible **crystal collimation** at the LHC were introduced.

*Beam tests in the LHC deemed necessary before relying on this promising technique for LHC upgrades and for other machines.*

- ☑ A setup for crystal collimation studies has been **installed** in the LHC collimation insertion region for **beam tests** starting in **2015!**

*We believe that we can learn a lot for a minimum-impact installation setup with goniometers for horizontal and vertical beam tests.*

*Other outstanding open points will follow this “first phase” at low intensities.*

- ☑ **Goals for beam tests** at the LHC and **plans for 2015** were discussed

*It will be challenging to fit more than a few shifts into the busy LHC schedule  
→ more important than in the past to start with a “debugged” setup.*



- ☑ The present **LHC collimation system**, and highlight of its main performance achievements, were presented.

*We are very happy with the performance up to 4 TeV → legacy for upgrades!  
We need to monitor carefully the behaviour at higher energies (quenches!)*

- ☑ Scope of a possible **crystal collimation** at the LHC were introduced.

*Beam tests in the LHC deemed necessary before relying on this promising technique for LHC upgrades and for other machines.*

- ☑ A setup for crystal collimation studies has been **installed** in the LHC collimation insertion region for **beam tests** starting in **2015!**

*We believe that we can learn a lot for a minimum-impact installation setup with goniometers for horizontal and vertical beam tests.*

*Other outstanding open points will follow this “first phase” at low intensities.*

- ☑ **Goals for beam tests** at the LHC and **plans for 2015** were discussed

*It will be challenging to fit more than a few shifts into the busy LHC schedule  
→ more important than in the past to start with a “debugged” setup.*


- ☑ Looking forward to seeing channeled and collimated beam in 2015!



# *Reserve slides*




# The LHC stored energy challenge



J. Wenninger




# The LHC stored energy challenge




J. Wenninger

# The LHC stored energy challenge




J. Wenninger

# The LHC stored energy challenge




**Beam cleaning requirements at the LHC exceed previous machines by orders of magnitude!**

# The LHC stored energy challenge



**Beam cleaning requirements at the LHC exceed previous machines by orders of magnitude!**




B. Salvachua

- Excellent stability achieved with 1 alignment per year in IR3/6/7 (2x30 devices).
- New alignments are only repeated for **new physics configurations** (it remains crucial to be efficient!)
  - ➔ PhD by G. Valentino: average alignment time **< 5 min** per collimator using the BLMs.




# Stability of cleaning




B. Salvachua

- Excellent stability achieved with 1 alignment per year in IR3/6/7 (2x30 devices).
- New alignments are only repeated for **new physics configurations** (it remains crucial to be efficient!)
  - ➔ PhD by G. Valentino: average alignment time **< 5 min** per collimator using the BLMs.




# Handling 1 MW beam losses at 4 TeV!




Controlled beam excitation over several seconds: **Peak > 1 MW on TCP!**  
Worsened cleaning by relaxing collimator settings.

# Handling 1 MW beam losses at 4 TeV!





Controlled beam excitation over several seconds: **Peak > 1 MW on TCP!**  
Worsened cleaning by relaxing collimator settings.

# Handling 1 MW beam losses at 4 TeV!




Controlled beam excitation over several seconds: **Peak > 1 MW on TCP!**  
 Worsened cleaning by relaxing collimator settings.


# Handling 1 MW beam losses at 4 TeV!




several seconds: **Peak > 1 MW on TCP!**  
 relaxing collimator settings.



# Understanding of LHC beam losses



# Understanding of LHC beam losses



Note 7 orders of magnitude on y scale!

Excellent qualitative agreement: all critical loss locations identified.





# Predicted intensity reach from cleaning





# Predicted intensity reach from cleaning



- Considering a minimum lifetime of **0.2 h** based on the 2012 experience
  - *Perhaps pessimistic, but ~10% of fills reached  $\tau_b < 0.5-1h$ !*
  - *Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)*



# Predicted intensity reach from cleaning



- Considering a minimum lifetime of **0.2 h** based on the 2012 experience
  - *Perhaps pessimistic, but ~10% of fills reached  $\tau_b < 0.5-1h$ !*
  - *Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)*
- Different models to scale losses to 6.5 TeV: **Intensity reach from proton cleaning in IR7 is 3 to 6 times the nominal LHC ( $3.2 \times 10^{14}p$ ).**  
Less margin at 7 TeV (different for 2 available quench models).  
HL-LHC intensity goal reduce this window by a factor  $\sim 2$ .



# Predicted intensity reach from cleaning



- Considering a minimum lifetime of **0.2 h** based on the 2012 experience
  - Perhaps pessimistic, but  $\sim 10\%$  of fills reached  $\tau_b < 0.5-1h!$
  - Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)
- Different models to scale losses to 6.5 TeV: **Intensity reach from proton cleaning in IR7 is 3 to 6 times the nominal LHC ( $3.2 \times 10^{14}p$ ).**  
Less margin at 7 TeV (different for 2 available quench models).  
HL-LHC intensity goal reduce this window by a factor  $\sim 2$ .
- For more than a factor 2 above LHC design, we have to worry also about **collimator robustness!**  
*We might have to set BLM thresholds to protect the collimators!*



# Predicted intensity reach from cleaning



- Considering a minimum lifetime of **0.2 h** based on the 2012 experience
  - Perhaps pessimistic, but  $\sim 10\%$  of fills reached  $\tau_b < 0.5-1h!$
  - Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)
- Different models to scale losses to 6.5 TeV: **Intensity reach from proton cleaning in IR7 is 3 to 6 times the nominal LHC ( $3.2 \times 10^{14}p$ ).**  
Less margin at 7 TeV (different for 2 available quench models).  
HL-LHC intensity goal reduce this window by a factor  $\sim 2$ .
- For more than a factor 2 above LHC design, we have to worry also about **collimator robustness!**  
*We might have to set BLM thresholds to protect the collimators!*
- **Ions: ALICE luminosity upgrade target is at least a factor 2 above quench limits.**  
Same limitations apply for IR1 and IR5 that have less priority for ion runs.

- Considering a minimum lifetime of **0.2 h** based on the 2012 experience
  - Perhaps pessimistic, but  $\sim 10\%$  of fills reached  $\tau_b < 0.5-1h!$
  - Reviewers felt that it could get worse (25ns vs 50ns, higher E, larger impedance)
- Different models to scale losses to 6.5 TeV: Intensity reach from proton cleaning in IR7 is **3 to 6 times the nominal LHC** ( $3.2 \times 10^{14}p$ ).  
Less margin at 7 TeV (different for 2 available quench models).  
HL-LHC intensity goal reduce this window by a factor  $\sim 2$ .
- For more than a factor 2 above LHC design, we have to worry also about **collimator robustness!**  
*We might have to set BLM thresholds to protect the collimators!*
- Ions: ALICE luminosity upgrade target is at least a factor 2 above quench limits.  
Same limitations apply for IR1 and IR5 that have less priority for ion runs.
- No additional limitations in IR1/5 until LS3 from physics debris thanks to the use of 3 TCL collimators.  
*Expect the same result for HiLumi, but need to prove this with final IR layouts.  
Backup slide in case more details are needed. See also talk by L. Esposito.*

- **16 Tungsten TCTs** in all IRs and the **2 Carbon TCSGs** in IR6 will be replaced by **new collimators with integrated BPMs**.

**Gain:** can align the collimator jaw without “touching” the beam → no dedicated low-intensity fills.

→ *Drastically reduced setup time* => *more flexibility in IR configurations*

→ *Reduced orbit margins in cleaning hierarchy* => *more room to squeeze  $\beta^*$ :  $\geq \sim 30$  cm (R. Bruce)*

→ *Improved monitoring of local orbit and interlocking strategy*

- Updated **TCL layouts in IR1/5** for physics debris absorption

→ *Add 1-2 TCL collimator per beam*. Expected to be compatible with HL proton luminosity.


- Improve protection of warm MQW magnets in IR3 by adding **passive absorbers**

→ *Improve lifetime by a factor  $\sim 5$  and allow more flexibility for loss sharing IR3/IR7.*

- Other smaller improvements/consolidation works



→ *IR8 vacuum layout.*

→ *Replace a TCP that was heating.*



Courtesy O. Aberle, A. Bertarelli, F. Carra, A. Dallochio, L. Gentini et al.

# Collimator hierarchy and $\beta^*$ reach



- Closing down the collimators reduces the (normalized) triplet aperture that we can protect → can fit a smaller  $\beta^*$ :

$$\beta^* \propto \frac{1}{N_{mqx} \sigma_{mqx}}$$



$$N_{mqx} > N_{tct} > N_{tcdq} > N_{tcsg} > N_{tcp}$$

- Setting hierarchy was tightened after gaining **operational experience** and confidence in the machine (optics/orbit stability, beam lifetime, cleaning requirements, ....)
- Started with “relaxed” settings (easier commissioning, less challenging tolerance set), then achieved at 4 TeV gaps in mm equivalent to the **design 7TeV goal** →  $\beta^* = 60 \text{ cm!}$
- **Improve cleaning** performance but **reduce lifetime!**



# Lifetime during OP cycle

Couple of illustrative examples taken randomly from the LHC elogbook...



Will this be a serious issue after LS1?

Detailed analysis of quench tests will provide improved estimates.

Needs of possible scraping methods (hollow e-lens or similar) are being studied.


Can always open the collimators, at the **cost of larger  $\beta^*$** .

# Losses from luminosity debris


- In 2012, we have started using the TCL collimators in IP1 and IP5 that catch **physics debris**.
- Set to  $10\sigma$  since the start of the run.
- We have performed TCLs scans to understand the impact on reducing the losses and the load to the magnets. At  $10\sigma$  measured losses at Q8 reduced by a factor of 50!

Significant improvement of SEU's in IR1 and IR5

## Proton operation in 2011



## Proton operation in 2012




# 3.5 TeV losses with Pb-Pb collisions

Bound-free pair production secondary beams from IPs


IBS & Electromagnetic dissociation at IPs, taken up by momentum collimators

Losses from collimation inefficiency, nuclear processes in primary collimators




J. Jowett

# Secondary beam at the IR2 DS



Cannot separate BFPP and main beam in warm area  
(eg by Roman pots a la TOTEM).

# Secondary beam at the IR2 DS






# Lifetime analysis (ii)




## Beam lifetime 2011 Minimum lifetime per each fill



In 2011 we achieved very good beam lifetime, with few fills below 1 hour

Number of fills with  $I_{tot} > 10^{13}$  protons: 259 fills analyzed in 2011





# Lifetime analysis (i)




## Beam lifetime 2012

Minimum lifetime per each fill



2012

Note: filled markers corresponds to fills that dumped



Collimation Review 2013 - Belen Salvachua

Number of fills with  $I_{tot} > 10^{13}$  protons: 384 fills analyzed in 2012

# Minimum beam lifetime in 2012

Beam intensity versus time

$$I(t) = I_0 \cdot e^{-\frac{t}{\tau_b}}$$

Beam lifetime gives the loss rate on collimators. Cleaning  $\eta$  gives the peak losses in magnets.

**Collimator design: 500 KW!**

*Minimum (assumed)  
beam lifetime*

$$N_{\text{tot}} = \frac{\tau_b R_q}{\tilde{\eta}_c}$$

*Quench limit of  
SC magnets*

*Collimation cleaning at  
limiting cold location*



# Minimum beam lifetime in 2012

Beam intensity versus time

$$I(t) = I_0 \cdot e^{-\frac{t}{\tau_b}}$$

Beam lifetime gives the loss rate on collimators. Cleaning  $\eta$  gives the peak losses in magnets.

**Collimator design: 500 KW!**


Minimum (assumed) beam lifetime

$$N_{\text{tot}} = \frac{\tau_b R_q}{\tilde{\eta}_c}$$

Quench limit of SC magnets

Collimation cleaning at limiting cold location

**2012: Minimum lifetime with gaps equiv. to 7 TeV: 0.2 - 1 hour**



B. Salvachua

See talk by E. Métral: to what extent this depends on collimators?